

Safety Data Sheet

240461 Ovi-mark, blue

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: 240461 Ovi-mark, blue

Article no

Article no	Description
240461	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: #Not translated#

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Jørgen Kruuse A/S
Address: Havretoften 4
Zip code: 5550 Langeskov
Country: DENMARK
E-mail: info@kruuse.com, kruuse.norge@kruuse.com, kruuse.svenska@kruuse.com
Phone: +4572141511
Fax: +4572141600

1.4. Emergency Telephone Number

0870 600 6266 (UK only) Only available to health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Aerosol 1;H222 Aerosol 1;H229 Skin Irrit. 2;H315 Acute Tox. 4;H332 STOT SE 3;H336 Aquatic Chronic 2;H411

Most serious harmful effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Harmful if inhaled. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system.

2.2. Label elements

Pictograms



Safety Data Sheet

240461 Ovi-mark, blue

Signal word: Danger

Contains

Substance: Naphtha (petroleum), hydrotreated light, low boiling point

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

2.3. Other hazards

The product does not contain any PBT or vPvB substances.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS number	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
Naphtha (petroleum), hydrotreated light, low boiling point	64742-49-0	265-151-9		30 - 50%		Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411
propane	74-98-6	200-827-9		30 - 50%		Flam. Gas 1;H220 Press. Gas Comp. gas;H280
Butane	106-97-8	203-448-7		10 - 30%		Flam. Gas 1;H220 Press. Gas liq. gas;H280
Isobutane	75-28-5	200-857-2		1 - 10%		Flam. Gas 1;H220 Press. Gas Comp. gas;H280

Please see section 16 for the full text of R-phrases and H-phrases.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of discomfort.

Skin contact: Remove contaminated clothing. Wash the skin thoroughly with water and continue washing for a long time. Seek medical advice in case of persistent discomfort.

Safety Data Sheet

240461 Ovi-mark, blue

Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
Burns:	Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.
General:	When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. Irritating to skin - may cause reddening. Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system. Inhalation of spray mist may cause chemical pneumonia. Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. Harmful by inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media:	Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.
Unsuitable extinguishing media:	Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Explosive mixtures may form with air when heated/exposed to fire. CAUTION! Aerosol containers may explode.

5.3. Advice for fire-fighters

Wear Self-Contained Breathing Apparatus (SCBA) with chemical resistant gloves. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Stay upwind/keep distance from source. Keep unnecessary personnel away. Provide adequate ventilation. Smoking and naked flames prohibited. Wear safety goggles if there is a risk of eye splash. Wear gloves. In case of insufficient ventilation, wear respiratory protective equipment.
For emergency responders:	In addition to the above: Protective suit equivalent to EN 368, type 3, is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

6.3. Methods and material for containment and cleaning up

Wipe up drops and splashes with a cloth. Provide good ventilation.

6.4. Reference to other sections

Safety Data Sheet

240461 Ovi-mark, blue

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy. Smoking and naked flames prohibited. Wash hands before breaks, before using restroom facilities, and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep in tightly closed original packaging. Avoid direct sunlight.

Do not store with the following: Strong oxidisers/ Strong acids.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Substance name	Time period	ppm	mg/m3	Comment	Remarks
Butane	8h	600	1.450		
Butane	15m	750	1.810		

Measuring methods: Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

Legal basis: EH40/2005 Workplace exposure limits. Last amended December 2011.

8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles if there is a risk of eye splash. Eye protection must conform to EN 166.

Personal protective equipment, hand protection: Wear gloves. Type of material: Butyl rubber. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374.

Personal protective equipment, skin protection: Wear suitable protective clothing.

Personal protective equipment, respiratory protection: In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A/AX. Respiratory protection must conform to one of the following standards: EN 136/140/145.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Safety Data Sheet

240461 Ovi-mark, blue

Parameter	Value/unit
State	Aerosol
Colour	Blue
Odour	Characteristic
Solubility	No data
Explosive properties	No data
Oxidising properties	No data

Parameter	Value/unit	Remarks
pH (solution for use)	No data	
pH (concentrate)	No data	
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flash Point	-60 °C	
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	No data	
Vapour pressure	No data	
Vapour density	No data	
Relative density	No data	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
Viscosity	No data	
Odour threshold	No data	

9.2 Other information

Other Information: None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Strong oxidisers/ Strong acids.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

Product vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid direct sunlight. Avoid heating and contact with ignition sources.

10.5. Incompatible materials

Strong oxidisers/ Strong acids.

Safety Data Sheet

240461 Ovi-mark, blue

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Naphtha (petroleum), hydrotreated light, low boiling point

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 2000mg/kg			

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - dermal

Naphtha (petroleum), hydrotreated light, low boiling point

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		2000 mg/kg			

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation

Naphtha (petroleum), hydrotreated light, low boiling point

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4 h	5 mg/l			

Harmful by inhalation.

Skin corrosion/irritation: Irritating to skin - may cause reddening.

Serious eye damage/eye irritation: Temporary irritation. The product does not have to be classified. Test data are not available.

Respiratory sensitisation or skin sensitisation: The product does not have to be classified. Test data are not available.

Germ cell mutagenicity: The product does not have to be classified. Test data are not unequivocal.

Carcinogenic properties: The product does not have to be classified. Test data are not available.

Reproductive toxicity: The product does not have to be classified. Test data are not available.

Single STOT exposure: The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

Repeated STOT exposure: The product does not have to be classified. Test data are not available.

Aspiration hazard: Inhalation of spray mist may cause chemical pneumonia. The product does not have to be classified. Test data are not available.

Safety Data Sheet

240461 Ovi-mark, blue

Other toxicological effects: None known.

SECTION 12: Ecological information

12.1. Toxicity

Naphtha (petroleum), hydrotreated light, low boiling point

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute algae		72 h	IC50	< 10mg/l			
Acute Daphnia		48 h	EC50	< 10mg/l			
Acute fish		96 h	LC50	< 10mg/l			

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Test data are not available.

12.3. Bioaccumulative potential

Test data are not available.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Avoid unnecessary release to the environment. Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility with the specifications set out below.

Aerosol sprays: EWC code: 16 05 04 Gases in pressure containers containing dangerous substances. Wiping cloths with organic solvents: EWC code: 15 02 02 Absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN-No.: 1950
14.2. UN proper shipping name: AEROSOLS

14.4. Packing group:
14.5. Environmental hazards:

The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.

14.3. Transport hazard class(es): 2.1
Hazard label(s): 2.1

Safety Data Sheet

240461 Ovi-mark, blue

Hazard identification number:

Tunnel restriction code: D

Other Information: -

Inland water ways transport (ADN)

14.1. UN-No.: 1950
14.2. UN proper shipping name: AEROSOLS

14.4. Packing group:

14.5. Environmental hazards: The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.

14.3. Transport hazard class(es): 2.1

Hazard label(s): 2.1

Environmentally hazardous in tank vessels:

Other Information: -

Sea transport (IMDG)

14.1. UN-No.: 1950
14.2. UN proper shipping name: AEROSOLS

14.4. Packing group:

14.5. Environmental hazards: The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l.

14.3. Transport hazard class(es): 2.1

Hazard label(s): 2.1

EmS: F-D, S-U

Environmental Hazardous Substance Name(s):

IMDG Code segregation group: - None -

Other Information: -

Air transport (ICAO-TI / IATA-DGR)

14.1. UN-No.: 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.4. Packing group:

14.5. Environmental hazards:

14.3. Transport hazard class(es): 2.1

Hazard label(s): 2.1

Other Information:

14.6. Special precautions for user

None.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: Directive 2012/18/EU (Seveso), P3a FLAMMABLE AEROSOLS: Column 2: 150 (net) t, Column 3: 500 (net) t.

Statutory order about work performance no. 559/2004, latest amended by no. 627/2015.

Safety Data Sheet

240461 Ovi-mark, blue

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	18/06/2015	Sidsel Rue	Udarbejdelse

Abbreviations:
PBT: Persistent, Bioaccumulative and Toxic
vPvB: Very Persistent and Very Bioaccumulative
STOT: Specific Target Organ Toxicity

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Training advice: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method: Calculation based on the hazards of the known components.

List of relevant H-statements

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure, may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Quality assurance of SDS: HSV/ Bureau Veritas HSE Denmark A/S

SDS is prepared by

Company: Bureau Veritas HSE Denmark A/S
Address: Birkemosevej 7
Zip code: 6000 Kolding
Country: DENMARK
Document language: GB